

S87E 20.77 ch

N3E 40.75

82.45 A.

S87W 20.20

S49W 40.75

July 3rd 1872

Surveyed June 21st 1872 in Sec. 11. T3R14
for T. M. Ara. Beginning at a stone in road and S E corner to G.
W. Aikens lands, and Running S4W 40.75 ch to the Sydney
Pike; Thence S87W 20.20 to S E corner of A R Horners land
Thence N3E 40.75 to a stone in a lane; Thence S87E 20.77 to
the place of beginning. Containing eighty-three (83) and
4/100 acres.

M W M Cormick.

Surveyor Logan Co. D.

6507

1P

INDEXED ON MAP

Ed. Hurst Survey March 15th 1917
 Ed. Hurst }
 T.I. Murphy } Chairmen.

- (1) Start cent pike S 95° E Hurst in line wire fence
 Thence with cent pike S 84 3/4° E. = at 20.25 ch stone
 set by one. Boulder 10" x 7" x 6" in cent Tp Road 1/2 pike
- (2) Start at stone 20.28 of (1). With Tp road N 6 1/4° E.
 at 15.00 ch at boulder 18" x 7" x 5" at 3/2 W of cent gravel.
- (3) Start cent pike S E < Gobby = 0 of 1.
 Thence with wire fence Co. line Gobby.
 at 15.00 ch at stone on E side fence. Boulder
- (4) Start at stone = 15.00 of (3) Thence S 84 3/4° E.
 at 10.04. set boulder 15" x 7" x 6" at <
 20.52
 20.55 stone Tp Road = 15.00 of 2
- (5) Start at 10.04 of (4). thence N 5 1/2° E.
 at 9.43 set pole
- (6) Start at stone 15.00 of (3) with fence Co. line Gobby.
 N 5 1/2° E At 9.43 feet in stone, 17" x 10" x 7" at wire fence
- (7) Start at stone 9.43 of (6). S 84 3/4° E.
 at 5.00 set stone 5" x 10" x 12" in line for fence
 at 10.04 set stake in N side ditch at 3/2 N. cent ditch
- (8) Start at stone N E 3 = 15.00. S 5 1/2° W = at 7.00 set 7.
- (9) Start at S E < Gobby in cent pike.
 Thence with pike S 84 3/4° E. = 10.88 to S E < Hurst
 set stone 8" x 6" x 6" in center pike for <
- (10) Start at stone 10.88 of (9). Meas N 82 7° at stone 12.26 x
- (11) " " S E < Gobby Meas N 82 7° set stone at same
 fence stone 18" x 13" x 8". E of Sig stone. Wire fence

Plat Ed. Hurst Survey.
 Mar. 17-1917.
 Part SE 1/4 Sec 11 T. 3. R. 14. Harrison Tp.

