

LIBERTY TOWNSHIP RD. 30

	+	HI	-	ELEV	CORR. ELEV.
Bm ₁	8.96	1155.94		1146.98	
	11.65	1162.40	8.19	1150.75	
TP ₂	11.09	1172.96	0.53	1161.87	
	7.67	1180.37	0.26	1172.70	
	0.51	1169.65	11.23	1169.14	C.R. bet
	0.65	1160.88	9.42	1160.23	
	1.72	1156.48	6.12	1158.76	
	11.35	1167.57	0.26	1156.22	
	10.96	1178.38	0.15	1167.42	
	5.28	1182.60	1.06	1177.32	Sw. 6' bet. Str.
	7.34	1189.63	0.31	1182.29	
	6.20	1193.15	0.68	1188.95	
	6.47	1194.89	6.73	1188.42	
Bm ₂			1.31	1193.58	1193.60
	(CHECK)				
Bm ₂	1.22	1194.80		1193.58	
	6.42	1194.79	6.43	1188.37	
	0.86	1190.05	5.60	1189.19	
T.P.			1.12	1188.93	
	0.04	1182.32	7.77	1182.28	
	0.22	1171.16	11.38	1170.94	
	0.13	1160.71	10.58	1160.58	
	2.81	1156.02	7.50	1153.21	

Dodson
Little
Nichols

3/18/68

11

Bm₁: RR spike in power pole 25' Lt. of Sta. 0+18
@ N.W. Cor. T.R. 30 & T.R. 32
T.P.₂ - Date nail in power pole, 300' W. of C.C.K. & J.L. R/W
line, on north side T.R. 30 [26]

INDEXED ON MAP

4347

Bm₂ chiseled "□" E. end lower headwall @ N.E.
Cor. U.S.R. 68 & T.R. 30